

ULTRACARE MOULD REMOVER

High penetration detergent for mould removal, with immediate effect



WHERE TO USE

UltraCare Mould Remover is an innovative formulation to be used for treating surfaces deteriorated by moulds and algae.

It quickly removes moulds and hygienises stone surfaces, stone, render (including painted render), cement, Terracotta, grouts, ceramic, glass and klinker.

TECHNICAL CHARACTERISTICS

UltraCare Mould Remover quickly removes moulds when applied on the surface of the material to be treated.

RECOMMENDATIONS

- Do not spray on metal surfaces, wood, plants or fabric. In case of accidental contact, wash thoroughly with clean water.
- Do not use on polished stone.
- Due to the very wide range of materials available on the market, we recommend carrying out a preliminary test on a hidden part of the surface, in order to evaluate the compatibility of the product before applying it on the whole surface (especially to verify possible colour variations on decorative coatings).
- It is advisable to use suitable protective clothing during application. If applied in interior, make sure the environment is well aerated.

APPLICATION PROCEDURE

The product is ready to use and does not need to be diluted with water. Shake well before application. Spray directly on the surface to clean holding the bottle in vertical position at approx. 20 cm distance. Spread the product evenly on the surface to be treated using a cloth to make it penetrate correctly. Remove any excess of product to avoid dripping.

For a stronger effect it is possible to apply the product more than once by repeating the procedure described above and waiting at least 15 minutes between each application.

After cleaning (wait at least 10 minutes) rinse the surface using a cloth or sponge dampened with only clean water.

CONSUMPTION

0.75 l of **UltraCare Mould Remover** can treat up to 15 m² of surface (one coat). Yield is heavily influenced by the absorbency level and the surface finish of the substrate to be treated.

PACKAGING

UltraCare Mould Remover is supplied in 0.75 l spray bottles.

STORAGE

UltraCare Mould Remover may be stored for 2 years in its original packaging.

SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATION

Instructions on the safe use of our products can be found on the latest version of the Safety Data Sheet, available from our website www.mapei.com.

PRODUCT FOR PROFESSIONAL USE

TECHNICAL DATA (typical values)

Physical and chemical properties

Use:	mould remover
Appearance:	liquid
Colour:	transparent
Odour:	characteristic
Relative density [UoM]:	1.13 g/cm ³
pH:	13

WARNING

Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.

Please refer to the current version of the Technical Data Sheet, available from our website www.mapei.com

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in force at the time of the MAPEI product installation.

The most up-to-date TDS can be downloaded from our website www.mapei.com.

ANY ALTERATION TO THE WORDING OR REQUIREMENTS CONTAINED OR DERIVED FROM THIS TDS EXCLUDES THE RESPONSIBILITY OF MAPEI.

11018-9-2022-I-en

Any reproduction of texts, photos and illustrations published here is prohibited and subject to prosecution

