

Safety Data Sheet
PURTOP EASY

Safety Data Sheet dated: 15/09/2023 - version 3



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: PURTOP EASY

Trade code: 904UE9990

UFI: 9D21-U00X-T008-YVQA

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Polyurethane for waterproofing and protection

Uses advised against: Not available

1.3. Details of the supplier of the safety data sheet

Company: MAPEI U.K. Ltd - Mapei House Steel Park Road
Halesowen - West Midlands B62 8HD

phone: +44(0)121 508 6970 - fax: +44(0)121 5086 960 - www.mapei.co.uk (office hour 8:30-17:30)

Responsible: sicurezza@mapei.it

1.4. Emergency telephone number

call NHS 111 or a doctor/OHES Environmental Ltd +44(0)333 333 9962

SECTION 2: Hazards identification



2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

Flam. Liq. 3 Flammable liquid and vapour.

Skin Irrit. 2 Causes skin irritation.

Eye Irrit. 2 Causes serious eye irritation.

Skin Sens. 1 May cause an allergic skin reaction.

STOT RE 2 May cause damage to organs through prolonged or repeated exposure.

2 The concentration of isocyanate stated is the percentage by weight of the free monomer calculated with reference to the total weight of the mixture.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Regulation (EC) No 1272/2008 (CLP):

Hazard pictograms and Signal Word



Warning

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/clothing and eye/face protection.

P370+P378 In case of fire, use a dry powder fire extinguisher to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

Special Provisions:

EUH204 Contains isocyanates. May produce an allergic reaction.

Contains

2,4-Diisocyanatotoluene-polypropylene glycol copolymer

xylene

Special provisions according to Annex XVII of REACH and subsequent amendments:

None.

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration $\geq 0.1\%$

Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients**3.1. Substances**

Not Relevant

3.2. Mixtures

Mixture identification: PURTOP EASY

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number
≥ 25 - < 50 %	2,4-Diisocyanatotoluene-polypropylene glycol copolymer	CAS:37273-56-6, 103837-43-0 EC:609-378-7	Eye Irrit. 2, H319; Skin Sens. 1, H317	
≥ 10 - < 20 %	xylene	CAS:1330-20-7 EC:215-535-7 Index:601-022-00-9	Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT RE 2, H373; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	01-2119488216-32-XXXX

SECTION 4: First aid measures**4.1. Description of first aid measures**

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

In case of fire, use a dry powder fire extinguisher to extinguish.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non emergency personnel:

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

For emergency responders:

Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

Retain contaminated washing water and dispose it.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

7.2. Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Community Occupational Exposure Limits (OEL)

xylene
CAS: 1330-20-7

OEL Type	Country	Occupational Exposure Limit
National	SWEDEN	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm SWEDEN, Short term value, 15 minutes average value
National	FINLAND	Long Term: 220 mg/m ³ - 50 ppm; Short Term: 440 mg/m ³ - 100 ppm FINLAND, hud
National	NORWAY	Long Term: 108 mg/m ³ - 25 ppm NORWAY, H
EU		Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm Skin
National	NORWAY	Long Term: 109 mg/m ³ - 25 ppm; Short Term: 218 mg/m ³ - 50 ppm
ACGIH		Long Term: 100 ppm; Short Term: 150 ppm A4, BEI - URT and eye irr, CNS impair
DFG	GERMANY	Short Term: Ceiling - 880 mg/m ³ - 200 ppm
ACGIH		Long Term: 100 ppm; Short Term: 150 ppm A4 - Not Classifiable as a Human Carcinogen; CNS impairment; eye and upper respiratory tract irritation
National	SWEDEN	Long Term: 221 mg/m ³ - 50 ppm
National	FRANCE	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm
National	SPAIN	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm
National	GREECE	Long Term: 435 mg/m ³ - 100 ppm; Short Term: 650 mg/m ³ - 150 ppm
National	DENMARK	Long Term: 109 mg/m ³ - 25 ppm
National	FINLAND	Long Term: 220 mg/m ³ - 50 ppm; Short Term: 440 mg/m ³ - 100 ppm
National	GERMANY	Long Term: 440 mg/m ³ - 100 ppm
National	PORTUGAL	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm
National	NORWAY	Long Term: 108 mg/m ³ - 25 ppm; Short Term: 135 mg/m ³ - 37.5 ppm
National	BELGIUM	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm
NDS	POLAND	Long Term: 100 mg/m ³
NDSCh	POLAND	Short Term: 200 mg/m ³
CHE	SWITZERLAND	Short Term: 870 mg/m ³ - 200 ppm
NDS	NETHERLANDS	Long Term: 210 mg/m ³ ; Short Term: 442 mg/m ³
National	CZECH REPUBLIC	Long Term: 200 mg/m ³
National	HUNGARY	Long Term: 221 mg/m ³ ; Short Term: 442 mg/m ³
Malaysia a OEL	MALAYSIA	Long Term: 434 mg/m ³ - 100 ppm
National	ESTONIA	Long Term: 200 mg/m ³ - 50 ppm; Short Term: 450 mg/m ³ - 100 ppm
National	LATVIA	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm
National	CZECH REPUBLIC	Short Term: Ceiling - 400 mg/m ³
National	SLOVAKIA	Short Term: Ceiling - 442 mg/m ³
National	SLOVAKIA	Long Term: 221 mg/m ³ - 50 ppm
National	SLOVENIA	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm
National	UNITED KINGDOM	Long Term: 220 mg/m ³ - 50 ppm; Short Term: 441 mg/m ³ - 100 ppm
National	BULGARIA	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm
National	ROMANIA	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm
TUR	TURKEY	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm
National	LITHUANIA	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm
National	CROATIA	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm
EU		Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm Behaviour Indicative Possibility of significant uptake through the skin (pure)

Biological limit values

xylene
CAS: 1330-20-7 Biological Indicator: Methyl uric Acid; Sampling Period: End of turn
Value: 1.5 GGCREAT; Medium: Urine

Predicted No Effect Concentration (PNEC) values

xylene
CAS: 1330-20-7 Exposure Route: Fresh Water; PNEC Limit: 0.327 mg/l

Exposure Route: Marine water; PNEC Limit: 0.327 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 12.46 mg/kg

Exposure Route: Marine water sediments; PNEC Limit: 12.46 mg/kg

Exposure Route: Soil; PNEC Limit: 2.31 mg/kg

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 6.58 mg/l

Exposure Route: Intermittent release; PNEC Limit: 0.32 mg/l

Derived No Effect Level (DNEL) values

xylene
CAS: 1330-20-7 Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects
Worker Industry: 289 mg/m³; Consumer: 174 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
Worker Industry: 289 mg/m³; Consumer: 174 mg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Industry: 180 mg/kg; Consumer: 108 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Industry: 77 mg/m³; Consumer: 14.8 mg/m³

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 1.6 mg/kg

8.2. Exposure controls

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; EN ISO 374:

Polychloroprene - CR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Nitrile rubber - NBR: thickness $\geq 0,35\text{mm}$; breakthrough time $\geq 480\text{min}$.

Butyl rubber - IIR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Fluorinated rubber - FKM: thickness $\geq 0,4\text{mm}$; breakthrough time $\geq 480\text{min}$.

Neoprene gloves are suggested (0,5 mm) not recommended gloves: not waterproof gloves

Respiratory protection:

Personal Protective Equipment should comply with relevant CE standards (as EN ISO 374 for gloves and EN ISO 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to appropriate EN standards, like EN 136, 140, 143, 149, 14387 for information on selection and use of appropriate respiratory protection equipment.

In case of insufficient ventilation use mask with ABEKP filters (EN 14387).

Hygienic and Technical measures

Not available

Appropriate engineering controls:

Not available

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state: Liquid

Appearance: Viscous

Color: various

Odour: Not available

Melting point / freezing point: Not available

Initial boiling point and boiling range: Not available

Flammability: The product is classified Flam. Liq. 3 H226

Lower and upper explosion limit: Not available
Flash point: 30 °C (86 °F)
Auto-ignition temperature: Not available
Decomposition temperature: Not available
pH: Not available
Viscosity: 3,000.00 cPs
Kinematic viscosity: Not available
Solubility in water: Not available
Solubility in oil: Not available
Partition coefficient (n-octanol/water): Not available
Vapour pressure: Not available
Relative density: 1.40 g/cm³
Vapour density: Not available

Particle characteristics:

Particle size: Not available

9.2. Other information

Miscibility: Not available
Conductivity: Not available
No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological Information of the Preparation

a) acute toxicity	Not classified Based on available data, the classification criteria are not met
b) skin corrosion/irritation	The product is classified: Skin Irrit. 2(H315)
c) serious eye damage/irritation	The product is classified: Eye Irrit. 2(H319)
d) respiratory or skin sensitisation	The product is classified: Skin Sens. 1(H317)
e) germ cell mutagenicity	Not classified Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified Based on available data, the classification criteria are not met
g) reproductive toxicity	Not classified Based on available data, the classification criteria are not met
h) STOT-single exposure	Not classified Based on available data, the classification criteria are not met
i) STOT-repeated exposure	The product is classified: STOT RE 2(H373)
j) aspiration hazard	Not classified Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

2,4-Diisocyanatotoluene- a) acute toxicity LD50 Oral Rat > 5000 mg/kg
polypropylene glycol
copolymer
LC50 Inhalation Rat > 3.82 mg/l 4h

xylene	a) acute toxicity	LD50 Oral Rat > 2000 mg/kg LC50 Inhalation Vapour Rat = 11 mg/l 4h LD50 Skin Rabbit = 3200 mg/kg LD50 Skin Rabbit > 4350 mg/kg LC50 Inhalation Rat = 29.08 mg/l 4h LD50 Oral Rat = 3500 mg/kg
	e) germ cell mutagenicity	NOAEL Inhalation Rat > 2000 ppm
	f) carcinogenicity	NOAEL Oral Rat = 500 mg/kg NOAEL Oral Rat = 1000 mg/kg
	g) reproductive toxicity	NOAEL Inhalation Rat = 500 ppm

11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration $\geq 0.1\%$

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

Not classified for environmental hazards.

Based on available data, the classification criteria are not met

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
2,4-Diisocyanatotoluene-polypropylene glycol copolymer	CAS: 37273-56-6, 103837-43-0 - EINECS: 609-378-7	c) Bacteria toxicity : EC50 > 10000 mg/L
xylene	CAS: 1330-20-7 - EINECS: 215-535-7 - INDEX: 601-022-00-9	a) Aquatic acute toxicity : EC50 Daphnia = 165 mg/L 48 a) Aquatic acute toxicity : LC50 Fish > 2 mg/L 96 a) Aquatic acute toxicity : EC50 Algae = 2.2 mg/L 72 c) Bacteria toxicity : EC50 = 96 mg/L 24 b) Aquatic chronic toxicity : NOEC Fish > 1.3 mg/L b) Aquatic chronic toxicity : NOEC Daphnia = 1.57 mg/L a) Aquatic acute toxicity : LC50 Fish Pimephales promelas = 13.4 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss 2.661 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss 13.5 mg/L 96h IUCLID a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus 13.1 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus = 19 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus 7.711 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Pimephales promelas 23.53 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Cyprinus carpio = 780 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Cyprinus carpio > 780 mg/L 96h IUCLID a) Aquatic acute toxicity : LC50 Fish Poecilia reticulata 30.26 mg/L 96h EPA a) Aquatic acute toxicity : EC50 Daphnia water flea = 3.82 mg/L 48h a) Aquatic acute toxicity : LC50 Daphnia Gammarus lacustris = 0.6 mg/L 48h

12.2. Persistence and degradability

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT, vPvB or endocrine disruptor substances present in concentration $\geq 0.1\%$

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration $\geq 0.1\%$

12.7. Other adverse effects

Not available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

A waste code (EWC) according to European List of Waste (LoW) cannot be specified, due to dependence on the usage. Contact and send to an authorized waste disposal service.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Hazardous waste: Yes

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

SECTION 14: Transport information

14.1. UN number or ID number

1139

14.2. UN proper shipping name

ADR-Shipping Name: COATING SOLUTION (includes surface treatments or coatings used for industrial or other purposes such as vehicle under coating, drum or barrel lining) (having a flash-point below 23 °C and viscous according to 2.2.3.1.4) (vapour pressure at 50 °C more than 110 kPa, boiling point of more than 35 °C) (xylene)

IATA-Technical name: COATING SOLUTION (includes surface treatments or coatings used for industrial or other purposes such as vehicle undercoating, drum or barrel lining) (xylene)

IMDG-Technical name: COATING SOLUTION (includes surface treatments or coatings used for industrial or other purposes such as vehicle under-coating, drum or barrel lining) (xylene)

14.3. Transport hazard class(es)

ADR-Class: 3

IATA-Class: 3

IMDG-Class: 3

14.4. Packing group

ADR-Packing Group: III

IATA-Packing group: III

IMDG-Packing group: III

14.5. Environmental hazards

Marine pollutant: No

Environmental Pollutant: No

IMDG-EMS: F-E, S-E

14.6. Special precautions for user

Road and Rail (ADR-RID):

ADR-Label: 3

ADR-Hazard identification number: 30

ADR-Special Provisions: -

ADR-Transport category (Tunnel restriction code): 3 (D/E)

ADR-Limited Quantity threshold: 5 L

Air (IATA):

IATA-Passenger Aircraft: 355

IATA-Cargo Aircraft: 366

IATA-Label: 3

IATA-Subsidiary hazards: -

IATA-Erg: 3L

IATA-Special Provisions: A3

Sea (IMDG):

IMDG-Stowage Code: Category A

IMDG-Stowage Note: -

IMDG-Subsidiary hazards: -

IMDG-Special Provisions: 955

IMDG-EMS: F-E, S-E

14.7. Maritime transport in bulk according to IMO instruments

Not Applicable

Transport in accordance with 2.2.3.1.5 of ADR and 2.3.2.5 of the IMDG Code.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC (2004/42/EC) : 265 g/l

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EU) n. 2020/878

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Regulation (EU) n. 2021/849 (ATP 17 CLP)

Regulation (EU) n. 2022/692 (ATP 18 CLP)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1	Lower-tier threshold (tonnes)	Upper-tier threshold (tonnes)
---	--------------------------------------	--------------------------------------

Product belongs to category: P5c	5000	
----------------------------------	------	--

		50000
--	--	-------

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: 3, 40

Restrictions related to the substances contained: 75

SVHC Substances:

SVHC substances not present in a concentration $\geq 0.1\%$ (w/w)

National regulations

Lagerklasse (TRGS-510): 3 - Flammable liquids

German Water Hazard Class.

2

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Code	Description
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
2.6/3	Flam. Liq. 3	Flammable liquid, Category 3
3.1/4/Dermal	Acute Tox. 4	Acute toxicity (dermal), Category 4
3.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4
3.10/1	Asp. Tox. 1	Aspiration hazard, Category 1
3.2/2	Skin Irrit. 2	Skin irritation, Category 2
3.3/2	Eye Irrit. 2	Eye irritation, Category 2
3.4.2/1	Skin Sens. 1	Skin Sensitisation, Category 1
3.8/3	STOT SE 3	Specific target organ toxicity — single exposure, Category 3
3.9/2	STOT RE 2	Specific target organ toxicity — repeated exposure, Category 2
4.1/C3	Aquatic Chronic 3	Chronic (long term) aquatic hazard, category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Flam. Liq. 3, H226	On basis of test data
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
Skin Sens. 1, H317	Calculation method
STOT RE 2, H373	Calculation method

If appropriate, specific provisions in relation to possible training for workers are mentioned in section 2. Any training related to safety in the workplace must in any case refer to a risk assessment that must be carried out by a company safety officer taking into account the specific operating and environmental conditions in which the products are used.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate
ATEmix: Acute toxicity Estimate (Mixtures)
BCF: Biological Concentration Factor
BEI: Biological Exposure Index
BOD: Biochemical Oxygen Demand
CAS: Chemical Abstracts Service (division of the American Chemical Society).
CAV: Poison Center
CE: European Community
CLP: Classification, Labeling, Packaging.
CMR: Carcinogenic, Mutagenic and Reprotoxic
COD: Chemical Oxygen Demand
COV: Volatile Organic Compound
CSA: Chemical Safety Assessment
CSR: Chemical Safety Report
DMEL: Derived Minimal Effect Level
DNEL: Derived No Effect Level.
DPD: Dangerous Preparations Directive
DSD: Dangerous Substances Directive
EC50: Half Maximal Effective Concentration
ECHA: European Chemicals Agency
EINECS: European Inventory of Existing Commercial Chemical Substances.
ES: Exposure Scenario
GefStoffVO: Ordinance on Hazardous Substances, Germany.
GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
IARC: International Agency for Research on Cancer
IATA: International Air Transport Association.
IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
IC50: half maximal inhibitory concentration
ICAO: International Civil Aviation Organization.
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG: International Maritime Code for Dangerous Goods.
INCI: International Nomenclature of Cosmetic Ingredients.
IRCCS: Scientific Institute for Research, Hospitalization and Health Care
KAFH: KAFH
KSt: Explosion coefficient.
LC50: Lethal concentration, for 50 percent of test population.
LD50: Lethal dose, for 50 percent of test population.
LDLo: Leathal Dose Low
N.A.: Not Applicable
N/A: Not Applicable
N/D: Not defined/ Not available
NA: Not available
NIOSH: National Institute for Occupational Safety and Health
NOAEL: No Observed Adverse Effect Level
OSHA: Occupational Safety and Health Administration
PBT: Persistent, Bioaccumulative and Toxic
PGK: Packaging Instruction
PNEC: Predicted No Effect Concentration.
PSG: Passengers
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
vPvB: Very Persistent, Very Bioaccumulative.
WGK: German Water Hazard Class.

Paragraphs modified from the previous revision:

- SECTION 2: Hazards identification
- SECTION 3: Composition/information on ingredients
- SECTION 5: Firefighting measures
- SECTION 6: Accidental release measures
- SECTION 7: Handling and storage

- SECTION 8: Exposure controls/personal protection
- SECTION 9: Physical and chemical properties
- SECTION 11: Toxicological information
- SECTION 12: Ecological information
- SECTION 14: Transport information
- SECTION 15: Regulatory information
- SECTION 16: Other information