

INSTARMAC

SAFETY DATA SHEET Ultrascape Slip Bond

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Ultrascape Slip Bond

1.2. Relevant identified uses of the substance or mixture and uses advised against

Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier Instarmac Group plc
Danny Morson Way
Birch Coppice Business Park
Dordon, Tamworth
Staffordshire. B78 1SE
United Kingdom
Tel: +44 (0) 1827 254400
Fax: +44 (0) 1827 285386
email@instarmac.co.uk www.instarmac.co.uk

1.4. Emergency telephone number

Emergency telephone +44(0)1827 254433 +44 (0)7971 217 347 (24 hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 STOT SE 3 - H335

Environmental hazards Not Classified

Human health See Section 11 for additional information on health hazards.

Environmental The product is not expected to be hazardous to the environment.

2.2. Label elements

Hazard pictograms



Signal word Danger

Hazard statements
H315 Causes skin irritation.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.

Ultrascape Slip Bond

Precautionary statements	<p>P261 Avoid breathing dust.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P272 Contaminated work clothing should not be allowed out of the workplace.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P310 Immediately call a POISON CENTER/ doctor.</p> <p>P312 Call a POISON CENTRE/doctor if you feel unwell.</p> <p>P321 Specific treatment (see medical advice on this label).</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p> <p>P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P403+P233 Store in a well-ventilated place. Keep container tightly closed.</p> <p>P405 Store locked up.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
---------------------------------	---

Contains PORTLAND CEMENT, CALCIUM FORMATE

Supplementary precautionary statements	<p>P261 Avoid breathing vapour/spray.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P272 Contaminated work clothing should not be allowed out of the workplace.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P312 Call a POISON CENTRE/doctor if you feel unwell.</p> <p>P321 Specific treatment (see medical advice on this label).</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p> <p>P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.</p> <p>P362 Take off contaminated clothing.</p> <p>P363 Wash contaminated clothing before reuse.</p> <p>P403+P233 Store in a well-ventilated place. Keep container tightly closed.</p> <p>P405 Store locked up.</p>
---	---

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.1. Substances

Classification according to EC 1272/2008 (CLP)

3.2. Mixtures

Quartz	30-60%
CAS number: 14808-60-7	EC number: 238-878-4
Classification	
Not Classified	

Ultrascape Slip Bond

PORTLAND CEMENT	30-60%
CAS number: 65997-15-1	EC number: 266-043-4
Classification Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1B - H317 STOT SE 3 - H335	
CALCIUM FORMATE	1-5%
CAS number: 544-17-2	EC number: 208-863-7
Classification Eye Dam. 1 - H318	

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Remove affected person from source of contamination. Get medical attention if any discomfort continues.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Give plenty of water to drink. Keep affected person under observation. Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel. Never give anything by mouth to an unconscious person.
Skin contact	Rinse immediately with plenty of water. Remove contaminated clothing. Get medical attention if any discomfort continues.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
----------------------------	---

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations.
-----------------------------	------------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Use fire-extinguishing media suitable for the surrounding fire.
-------------------------------------	---

5.2. Special hazards arising from the substance or mixture

Specific hazards	Not known. No unusual fire or explosion hazards noted.
Hazardous combustion products	Does not decompose when used and stored as recommended.

5.3. Advice for firefighters

Ultrascape Slip Bond

Protective actions during firefighting No specific firefighting precautions known.

Special protective equipment for firefighters Use protective equipment appropriate for surrounding materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up GENERAL. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. Collect and dispose of spillage as indicated in Section 13. See Section 11 for additional information on health hazards.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions No specific recommendations.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store at moderate temperatures in dry, well ventilated area.

Storage class Unspecified storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Quartz

Long-term exposure limit (8-hour TWA): WEL 0.3 mg/m³

PORTLAND CEMENT

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³

WEL = Workplace Exposure Limit.

Ingredient comments No exposure limits known for ingredient(s).

PORTLAND CEMENT (CAS: 65997-15-1)

DNEL

A derived no-effect level (DNEL) of 1 mg/m³ (as respirable dust) over an hour shift has been set.

CALCIUM FORMATE (CAS: 544-17-2)

Ingredient comments

No exposure limits known for ingredient(s).

Ultrascape Slip Bond

DNEL

Workers - Inhalation; Long term systemic effects: 337 mg/m³
 Industry - Inhalation; Short term systemic effects: 337 mg/m³
 Industry - Dermal; Long term systemic effects: 4780 mg/kg/day
 Industry - Dermal; Short term systemic effects: 4780 mg/kg/day
 Industry - Dermal; Long term local effects: 16.7 mg/cm²
 Industry - Dermal; Short term local effects: 16.7 mg/cm²
 General population - Inhalation; Long term systemic effects: 83.2 mg/m³
 General population - Inhalation; Short term systemic effects: 83.2 mg/m³
 General population - Dermal; Long term systemic effects: 2390 mg/kg/day
 General population - Dermal; Short term systemic effects: 2390 mg/kg/day
 General population - Dermal; Long term local effects: 8.3 mg/cm²
 General population - Dermal; Short term local effects: 8.3 mg/cm²
 General population - Oral; Long term systemic effects: 23.9 mg/kg/day

PNEC

- Fresh water; 2 mg/l
 - marine water; 0.2 mg/l
 - Sediment (Freshwater); 13.4 mg/kg
 - Sediment (Marinewater); 1.34 mg/kg
 - STP; 2.21 mg/l
 - Soil; 1.5 mg/kg
 Sediment and soil PNEC values are in mg/kg are 'dry weight' (dw).

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Not relevant.

Eye/face protection

The following protection should be worn: Chemical splash goggles.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures

Wash at the end of each work shift and before eating, smoking and using the toilet. No specific hygiene procedures recommended but good personal hygiene practices should always be observed when working with chemical products.

Respiratory protection

No specific recommendations. Respiratory protection may be required if excessive airborne contamination occurs.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Dusty powder.

9.2. Other information

Other information Not available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

Ultrascape Slip Bond

10.2. Chemical stability

Stability No particular stability concerns.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not applicable. No potentially hazardous reactions known.

10.4. Conditions to avoid

Conditions to avoid There are no known conditions that are likely to result in a hazardous situation.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects No information available.

General information No specific health hazards known.

Inhalation No specific health hazards known.

Ingestion May cause irritation. Symptoms following overexposure may include the following: Stomach pain. Nausea, vomiting. Diarrhoea.

Skin contact Irritating to skin.

Eye contact Irritating to eyes.

Acute and chronic health hazards This product may cause skin and eye irritation.

SECTION 12: Ecological information

Ecotoxicity There are no data on the ecotoxicity of this product.

12.1. Toxicity

Toxicity No information available

12.2. Persistence and degradability

Persistence and degradability No information available There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility The product is non-volatile.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

Ultrascape Slip Bond

12.6. Other adverse effects

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information When handling waste, the safety precautions applying to handling of the product should be considered.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

Not applicable.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Health and Safety at Work etc. Act 1974 (as amended).
Control of Substances Hazardous to Health Regulations 2002 (as amended).

Guidance Safety Data Sheets for Substances and Preparations.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information Only trained personnel should use this material.

Issued by HS&E Manager.

Ultrascape Slip Bond

Revision date	26/02/2021
Revision	2
Supersedes date	10/01/2018
SDS number	11224
SDS status	Approved.
Hazard statements in full	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H335 May cause respiratory irritation.

0