

Safety Data Sheet

KERAPOXY EASY DESIGN /B

Safety Data Sheet dated: 16/02/2024 - version 1



1. Identification

GHS Product Identifier

Mixture identification:

Trade name: KERAPOXY EASY DESIGN /B

Trade code: 905KB9999

Recommended use of the chemical and restrictions on use

Recommended use: Hardener for epoxy products

Uses advised against: Data not available.

Supplier's details

Company: MAPEI CONSTRUCTION CHEMICALS L.L.C

P.O. BOX 73869 DUBAI - United Arab Emirates

Office: 00971 4 8156666

Factory : 00971 4 8858428

Responsible: info@mapei.ae

Emergency phone number

Office: 00971 4 8156666

2. Hazard identification

Classification of the substance or mixture

Acute toxicity (oral), Category 5

May be harmful if swallowed

Skin corrosion, Category 1B

Causes severe skin burns and eye damage.

Serious eye damage, Category 1

Causes serious eye damage.

Skin Sensitisation, Category 1A

May cause an allergic skin reaction.

Acute aquatic hazard, category 1

Very toxic to aquatic life.

Chronic (long term) aquatic hazard, category 1

Very toxic to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

GHS label elements, including precautionary statements

Hazard pictograms and Signal Word



Danger

Hazard statements

H303 May be harmful if swallowed

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P273 Avoid release to the environment.

P280 Wear protective gloves/clothing and eye/face protection.

P301+P312 IF SWALLOWED: Call a POISON CENTER if you feel unwell.

P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P302+P352 IF ON SKIN: Wash with plenty of water.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310	Immediately call a POISON CENTER.
P333+P313	If skin irritation or rash occurs: Get medical advice.
P362+P364	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.
P501	Dispose of contents/container in accordance with applicable regulations.

Other hazards which do not result in a classification

No other hazards

3. Composition/information on ingredients

Substances

Not Relevant

Mixtures

Mixture identification: KERAPOXY EASY DESIGN /B

Hazardous components within the meaning of GHS and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number
≥25 - <50 %	Fatty acids C18 unsaturated, reaction products with tetraethylenepentamine	CAS:1226892-45-0, 68410-23-1 EC:629-725-6	Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Corr. 1C, H314; Skin Sens. 1A, H317	01-2119487006-38-XXXX
≥25 - <50 %	3-aminomethyl-3,5,5-trimethylcyclohexylamine	CAS:2855-13-2 EC:220-666-8 Index:612-067-00-9	Acute Tox. 4, H302; Eye Dam. 1, H318; Skin Corr. 1B, H314; Skin Sens. 1A, H317	01-2119514687-32-XXXX
≥5 - <10 %	Phenol, styrenated	CAS:61788-44-1 EC:262-975-0	Aquatic Chronic 2, H411	01-2119979575-18-XXXX
≥1 - <2.5 %	N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine	CAS:10563-29-8 EC:234-148-4	Acute Tox. 4, H302; Skin Corr. 1A, H314; Skin Sens. 1B, H317	01-2119970376-29-XXXX

4. First-aid measures

Description of necessary first-aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- OBTAIN IMMEDIATE MEDICAL ATTENTION.
- Remove contaminated clothing immediately and dispose of safely.
- After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

- Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

- Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

- Eye irritation
- Eye damages
- Skin Irritation
- Erythema

Indication of immediate medical attention and special treatment needed, if necessary

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media:

- Water.
- Carbon dioxide (CO2).

Unsuitable extinguishing media:

None in particular.

Special hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: N.A.

Explosive properties: N.A.

Oxidizing properties: N.A.

Special protective actions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. Accidental release measures**Personal precautions, protective equipment and emergency procedures**

Wear personal protection equipment.

Remove persons to safety.

Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

7. Handling and storage**Precautions for safe handling**

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

8. Exposure controls/personal protection**Control parameters****Community Occupational Exposure Limits (OEL)**

	OEL Type	Country	Occupational Exposure Limit
N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine CAS: 10563-29-8	RUS	RUSSIAN FEDERATION	Short Term: 1 mg/m ³

Predicted No Effect Concentration (PNEC) values

3-aminomethyl-3,5,5-trimethylcyclohexylamine
CAS: 2855-13-2

Exposure Route: Fresh Water; PNEC Limit: 0.06 mg/l

Exposure Route: Marine water; PNEC Limit: 0.006 mg/l

Exposure Route: Intermittent release; PNEC Limit: 0.23 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 5.784 mg/kg

Exposure Route: Marine water sediments; PNEC Limit: 0.578 mg/kg

Exposure Route: Soil; PNEC Limit: 1.121 mg/kg

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 3.18 mg/l

Phenol, styrenated
CAS: 61788-44-1

Exposure Route: Fresh Water; PNEC Limit: 0.001 mg/l

Exposure Route: Marine water sediments; PNEC Limit: 65778 mg/kg
Exposure Route: Freshwater sediments; PNEC Limit: 65778 mg/kg
Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 0.17 mg/l
Exposure Route: Soil; PNEC Limit: 31525 mg/kg

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine
CAS: 10563-29-8
Exposure Route: Fresh Water; PNEC Limit: 0.0092 mg/l

Exposure Route: Marine water; PNEC Limit: 0.00092 mg/l
Exposure Route: Intermittent release; PNEC Limit: 0.092 mg/l
Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 18.1 mg/l
Exposure Route: Freshwater sediments; PNEC Limit: 0.0336 mg/kg

Derived No Effect Level (DNEL) values

3-aminomethyl-3,5,5-trimethylcyclohexylamine
CAS: 2855-13-2
Exposure Route: Human Inhalation
Worker Industry: 20.1 mg/m³

Phenol, styrenated
CAS: 61788-44-1
Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Industry: 11.02 mg/m³; Consumer: 2.717 mg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Industry: 6.25 mg/kg; Consumer: 3.125 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 1.562 mg/kg

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine
CAS: 10563-29-8
Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Industry: 3.7 mg/m³; Consumer: 0.65 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
Worker Industry: 7.5 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
Worker Industry: 3.7 mg/m³; Consumer: 0.65 mg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Industry: 0.67 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 0.2 mg/kg

Appropriate engineering controls: N.A.

Individual protection measures, such as personal protective equipment (PPE)

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; EN ISO 374:

Polychloroprene - CR: thickness $\geq 0,5$ mm; breakthrough time ≥ 480 min.

Nitrile rubber - NBR: thickness $\geq 0,35$ mm; breakthrough time ≥ 480 min.

Butyl rubber - IIR: thickness $\geq 0,5$ mm; breakthrough time ≥ 480 min.

Fluorinated rubber - FKM: thickness $\geq 0,4$ mm; breakthrough time ≥ 480 min.

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Personal Protective Equipment should comply with relevant CE standards (as EN ISO 374 for gloves and EN ISO 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

9. Physical and chemical properties

Physical state Liquid

Color: light yellow

Appearance: paste

Odour: ammonia

Odour threshold: N.A.

pH: 11.00
Melting point / freezing point: N.A.
Initial boiling point and boiling range: N.A.
Flash point: N.A.
Evaporation rate: N.A.
Solid/gas flammability: N.A.
Upper/lower flammability or explosive limits: N.A.
Vapour pressure: 0.01
Vapour density: N.A.
Relative density: 1.10 g/cm³
Solubility in water: partly soluble
Solubility in oil: soluble
Partition coefficient (n-octanol/water): N.A.
Auto-ignition temperature: N.A.
Decomposition temperature: N.A.
Viscosity: 200,000.00 cPs

10. Stability and reactivity

Reactivity

Stable under normal conditions

Chemical stability

Data not available.

Possibility of hazardous reactions

None.

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

Hazardous decomposition products

None.

11. Toxicological information

Information on toxicological effects

Toxicological Information of the Preparation

a) acute toxicity	The product is classified: Acute toxicity (oral), Category 5(H303) ATEmix - Oral : 3361.46 mg/kg bw
b) skin corrosion/irritation	The product is classified: Skin corrosion, Category 1B(H314)
c) serious eye damage/irritation	The product is classified: Serious eye damage, Category 1(H318)
d) respiratory or skin sensitisation	The product is classified: Skin Sensitisation, Category 1A(H317)
e) germ cell mutagenicity	Not classified Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified Based on available data, the classification criteria are not met
g) reproductive toxicity	Not classified Based on available data, the classification criteria are not met
h) STOT-single exposure	Not classified Based on available data, the classification criteria are not met
i) STOT-repeated exposure	Not classified Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

Fatty acids C18 unsaturated, reaction products with tetraethylenepentamine	a) acute toxicity	LD50 Oral Rat > 2000 mg/kg
--	-------------------	----------------------------

3-aminomethyl-3,5,5-trimethylcyclohexylamine	a) acute toxicity	LC50 Inhalation Dust Rat > 5.01 mg/l 4h LD50 Oral Rat = 1030 mg/kg LD50 Skin Rat > 2000 mg/kg
Phenol, styrenated	a) acute toxicity	LC50 Inhalation Vapour Mouse = 158.3 mg/l 4h LD50 Oral Rat > 2500 mg/kg LD50 Skin Rat > 2000 mg/kg LD50 Skin Rabbit > 7940 mg/kg LC50 Inhalation Rat > 2.5 mg/l 6h LD50 Oral Rat 2100 mg/kg

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine	a) acute toxicity	LD50 Oral Rat = 1670 mg/kg
	b) skin corrosion/irritation	Skin Corrosive Skin Rabbit Positive
	d) respiratory or skin sensitisation	Skin Sensitization Skin Positive

12. Ecological information

Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

The product is classified: Acute aquatic hazard, category 1(H400), Chronic (long term) aquatic hazard, category 1(H410)

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
3-aminomethyl-3,5,5-trimethylcyclohexylamine	CAS: 2855-13-2 - EINECS: 220-666-8 - INDEX: 612-067-00-9	a) Aquatic acute toxicity : LC50 Fish = 110 mg/L 96
		a) Aquatic acute toxicity : EC50 Daphnia = 23 mg/L 48
		a) Aquatic acute toxicity : EC50 Daphnia = 388 mg/L 48
		a) Aquatic acute toxicity : EC50 Algae > 50 mg/L 72
		b) Aquatic chronic toxicity : NOEC Daphnia = 3 mg/L - 21 d
		a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna 14.6 mg/L 48h EPA
		a) Aquatic acute toxicity : EC50 Algae Desmodesmus subspicatus = 37 mg/L 72h IUCLID
		a) Aquatic acute toxicity : EC50 Daphnia = 4.6 mg/L 48
		a) Aquatic acute toxicity : EC50 Algae = 9.7 mg/L 72
		a) Aquatic acute toxicity : LC50 Fish = 5.6 mg/L 96
Phenol, styrenated	CAS: 61788-44-1 - EINECS: 262-975-0	a) Aquatic acute toxicity : LC50 Fish = 215 mg/L 96
		a) Aquatic acute toxicity : EC50 Daphnia = 9.2 mg/L 48
		a) Aquatic acute toxicity : EC50 Algae = 21 mg/L 72
		a) Aquatic acute toxicity : LC50 Fish Danio rerio > 100 mg/L 96h ECHA
		a) Aquatic acute toxicity : EC50 Daphnia = 9.2 mg/L 48
		a) Aquatic acute toxicity : EC50 Algae = 21 mg/L 72
		a) Aquatic acute toxicity : LC50 Fish Danio rerio > 100 mg/L 96h ECHA
		a) Aquatic acute toxicity : EC50 Daphnia = 9.2 mg/L 48
		a) Aquatic acute toxicity : EC50 Algae = 21 mg/L 72
		a) Aquatic acute toxicity : LC50 Fish Danio rerio > 100 mg/L 96h ECHA
N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine	CAS: 10563-29-8 - EINECS: 234-148-4	a) Aquatic acute toxicity : LC50 Fish = 215 mg/L 96
		a) Aquatic acute toxicity : EC50 Daphnia = 9.2 mg/L 48
		a) Aquatic acute toxicity : EC50 Algae = 21 mg/L 72
		a) Aquatic acute toxicity : LC50 Fish Danio rerio > 100 mg/L 96h ECHA
		a) Aquatic acute toxicity : EC50 Daphnia = 9.2 mg/L 48
		a) Aquatic acute toxicity : EC50 Algae = 21 mg/L 72
		a) Aquatic acute toxicity : LC50 Fish Danio rerio > 100 mg/L 96h ECHA
		a) Aquatic acute toxicity : EC50 Daphnia = 9.2 mg/L 48
		a) Aquatic acute toxicity : EC50 Algae = 21 mg/L 72
		a) Aquatic acute toxicity : LC50 Fish Danio rerio > 100 mg/L 96h ECHA

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

No Data found about other environmental hazard properties.

13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

14. Transport information

UN number

2735

UN proper shipping name

ADR-Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. (isophoronediamine - tetraethylenepentamine)

IATA-Technical name: AMINES, LIQUID, CORROSIVE, N.O.S. (isophoronediamine - tetraethylenepentamine)

IMDG-Technical name: AMINES, LIQUID, CORROSIVE, N.O.S. (isophoronediamine - tetraethylenepentamine)

Transport hazard class(es)

ADR-Class: 8

IATA-Class: 8

IMDG-Class: 8

Packing group, if applicable

Road and Rail (ADR-RID):

ADR-Label: 8

ADR-Packing Group: III

ADR-Hazard identification number: NA

ADR-Transport category (Tunnel restriction code): 3 (E)

ADR-Limited Quantity threshold: 5 L

Air (IATA):

IATA-Passenger Aircraft: 852

IATA-Cargo Aircraft: 856

IATA-Label: 8

IATA-Packing group: III

IATA-Subsidiary hazards: -

IATA-Erg: 8L

IATA-Special Provisions: A3 A803

Sea (IMDG):

IMDG-Packing group: III

IMDG-Stowage Code: Category A

IMDG-Stowage Note: SG35

IMDG-Subsidiary hazards: -

IMDG-Special Provisions: 223 274

IMDG-Page: N/A

IMDG-Label: N/A
IMDG-EMS: F-A, S-B
IMDG-MFAG: N/A

Environmental hazards

Marine pollutant: Yes
Environmental Pollutant: N.A.

Special precautions for user

N.A.

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

N.A.

15. Regulatory information

Safety, health and environmental regulations specific for the product in question

This Safety Data Sheet has been prepared according to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS), Fifth revised edition.

SCAQMD Rule 1113 : N.A.

SCAQMD Rule 1168: 2,8 (A+B)

16. Other information

Code	Description
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
3.1/4/Oral	Acute Tox. 4	Acute toxicity (oral), Category 4
3.2/1A	Skin Corr. 1A	Skin corrosion, Category 1A
3.2/1B	Skin Corr. 1B	Skin corrosion, Category 1B
3.2/1C	Skin Corr. 1C	Skin corrosion, Category 1C
3.3/1	Eye Dam. 1	Serious eye damage, Category 1
3.4.2/1A	Skin Sens. 1A	Skin Sensitisation, Category 1A
3.4.2/1B	Skin Sens. 1B	Skin Sensitisation, Category 1B
4.1/A1	Aquatic Acute 1	Acute aquatic hazard, category 1
4.1/C1	Aquatic Chronic 1	Chronic (long term) aquatic hazard, category 1
4.1/C2	Aquatic Chronic 2	Chronic (long term) aquatic hazard, category 2

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

Insert here further consulted bibliography

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

WGK: German Water Hazard Class.

KSt: Explosion coefficient.